

OREGON CORNER RESTORATION FORM

Section 21,22,27,28 Township 4N Range 37E W.M.
County Umatilla Date 8/1/93
CORNER DESIGNATION: R-13

Previous Renewals/Surveys, etc. The original survey was made by George S. Pershin under contract No. 332, dated July 29th, 1879. He set a fir post on N. descent for Cor. to Secs. 21,22,27 & 28.

A fir, 8 ins. diam. brs. N.34°E., 28 lks. dist.
A tamarack, 22 ins. diam. brs. S.14°E., 63 lks dist.
A fir, 6 ins. diam. brs. S.30°W., 36 lks. dist.
A fir, 15 ins. diam. brs. N.28°W., 22 lks dist.

As recorded on Land Corner Record Q-724 Umatilla County, Douglas Ferguson found a badly rotted tamarack stump from which he set a 5/8" x 30 steel pin with a plastic cap stamped LS 645 N.14°W., 63 lks.

A spruce 8" diam. brs. N.66°00'E., 38.67 ft. marked T4N R37E S22 BT
A white fir 9" diam. brs. S.58°30'E., 52.37 ft marked T4N R37E S27 BT
A spruce 9" diam. brs. S.72°30'W., 59.70 ft. marked T4N R37E S28 BT
A spruce 13" diam brs. N.43°30'W., 87.46 ft. marked T4N R37E S21 BT

Monument(s) & Accessories Found: (Condition and Source) Found a 1" iron pipe with a 2" brass cap marked as indicated in the monument detail and a 5/8" rebar with a plastic cap stamped LS 645 set in a mound of rocks.

A 10" spruce (pushed over) brs N.69°E., 39.1 ft. marked T4N R37E S22 BT
A 15" fir with visible scribing in a mostly closed blaze brs. S.53°E., 53.0 ft.

A 14" spruce stump with the bottom of a blaze on it brs. N.48°W., 88.0 ft.

Monument Detail:

T4N R37E
S21 + S22
S28 | S27
1977 ORE 422

Monument Set (Procedures and Description): The brass cap monument was solidly set and in good condition, so I maintained it by clearing away the brush and adding to the rock mound.

New Accessories:

A 11" fir brs. S.89°W., 29.0 ft. marked T4N R37E S28 BT
A 10" fir brs. N.54°W., 84.6 ft. marked T4N R37E S21 BT
A 27" fir brs. N.28°E., 67.6 ft. marked T4N R37E S22 BT
A steel fence post with a Land Survey Monument sign attached brs N.40°W., 3.7 ft.

Location & Comments: The corner is on a N. slope at the E. edge of a logging landing area.

Compass Declination: 18° E

Firm/agency: Tomkins-Wells Joint Venture
Land Surveying
P.O. Box 1696
Pendleton, Oregon 97801

Party Chief: Greg Flowers
Notes: Greg Flowers
Witness: Todd Rosenbalm

Surveyor's Seal

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106

expires 12-31-94

93-64-c