


History of original corner establishment:

Original survey was made by George S. Pershin under contract No. 332, dated July 29, 1879. The corner was set on August 29, 1879. He set a basalt stone 16 x 10 x 4 in a mound of stone in a small open glade on a south slope. He set the following bearing trees: A pine 20" dia. bears N 26 E, 107 lks. dist. A fir 8" dia. bears N 74 W, 70 lks. dist.



N

Description of corner evidence found:

I found a small open glade as described in the original GLO notes, and in the center of this glade there was a mound of stone, also evidence of an old fence cornering at this location and a location poster set by the Oregon State Highway people identifying this as the 1/4 corner common to Sections 27 & 28, though I could not identify the original stone and the bearing trees have rotted away or have been destroyed by logging operations, the position appeared to fit the original GLO calls, thus I tied the center of the mound of stone to my extensive co-ordinate system to confirm its position, of which I found to be harmonious with the surrounding found corners, thus accepted the collateral evidence as representing the position of the original 1/4 corner set by George S. Pershin in 1879.

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 5/8" x 30" steel pin, with a plastic cap stamped LS 645 in the center of the above mentioned mound of stone with the following new witness trees:
A pine 9" dia. bears S 44 10 W, 74.05 ft. and being scribed 1/4 S S28 BT.
A larch 8" dia. bears S 81 46 E, 93.19 ft. and being scribed 1/4 S S27 BT.

Note: The above described evidence was found and perpetuated by PLS 645. Then found and used by me, PLS 848 as controlling corners to the accompanying map of survey.



Office of..... County of.....
 State of..... I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by
 (COUNTY OFFICIAL) (DEPUTY)