


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

11

History of original corner establishment:

The original survey was made by George S. Pershin under contract No. 332, dated July 29, 1879. He set a fir post on the level for the corner location to sec's 26, 27 & 34, 35. He set the following bearing tree s:

A fir 8" dia. bears N 47 E, 62 lks. dist.
 A fir 8" dia. bears S 20 E, 10 lks. dist.
 A fir 24" dia. bears S 44 W, 34 lks. dist.
 A fir 20" dia. bears N 50 W, 42 lks. dist.



Description of corner evidence found:

I found remains of a dead tree bearing N 47 E, 62 lks. from assumed corner position
 I found remains of a dead tree bearing S 20 E, 10 lks from assumed corner position
 I found remains of a dead tree bearing S 44 W, 34 lks from assumed corner position
 I found remains of a dead tree bearing N 50 W, 42 lks from assumed corner position
 Finding these trees and scribing on portions thereof, I then restored the position of the original corner using the GLO bearing & distances as recorded by George S. Pershin.

Description of monument and accessories I established to perpetuate the original location of this corner

I set a mound of stone at the position of the section corner but did not set any new bearing trees.



Office of County of

State of, I hereby certify that the within instrument was filed in this office for record on the day of

..... by

(COUNTY OFFICIAL) (DEPUTY)